

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Aluminium Pigment ChemTech WZ15
Type of product : Pigment

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Dyestuff/pigment
Function or use category : Colouring agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chemical Technologies SIA
Ganibu Dambis 36, office 309
Riga, LV-1005
Latvia
T +371 6738 1303
info@chemtech.global - www.chemtech.global

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable solids, Category 1 H228

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable solid.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP) : Danger
Contains : Aluminium powder (stabilized)
Hazard statements (CLP) : H228 - Flammable solid.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P280 - Wear eye protection, protective gloves.

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P370+P378 - In case of fire: Use carbon dioxide (CO₂), alcohol resistant foam, dry extinguishing powder, dry sand to extinguish.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aluminium powder (stabilized)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1 REACH-no: 01-2119529243-45	93 – 97	Flam. Sol. 1, H228 Water-react. 2, H261
Silicon dioxide	CAS-No.: 7631-86-9 EC-No.: 231-545-4	2 – 4	Not classified
2-Propanol	CAS-No.: 67-63-0 EC-No.: 200-661-7	1 – 3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Comments

: Aluminium powder (stabilized): Depending on the packaging, grain size distribution or for other parameters, the physical classification of the product may differ if the relevant test data are available.
Water reactivity: based on test data according to N.5. of UN RTDG Handbook of Tests and Criteria, part III, subsection 33.4.1.4 the product does not emit flammable gases in contact with water.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Seek medical attention if ill effect or irritation develops.
First-aid measures after skin contact	: Wash skin with plenty of water. Remove contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: In case of contact, immediately rinse eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If necessary seek medical advice.
First-aid measures after ingestion	: IF SWALLOWED: Rinse mouth and call a POISON CENTER/doctor if you feel unwell.

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure.
Symptoms/effects after skin contact	: Product dust may cause mechanical irritation to the skin and mucous membranes.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating. redness, itching, tears.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Dry sand. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable solid.
Explosion hazard	: No direct explosion hazard.
Reactivity in case of fire	: May readily catch fire.
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Evacuate area. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: High temperature decomposition products are harmful by inhalation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation. Stop the leak. Sweep or shovel spills into appropriate container for disposal.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Avoid contact with eyes, skin and clothing. Ventilate spillage area. Do not touch or walk on the spilled product.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible. Collect spillage. Do not touch or walk on the spilled product. Avoid creating or spreading dust.
-----------------	---

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methods for cleaning up	: Mechanically recover the product. Sweep up or vacuum up the product.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Dust may form flammable and explosive mixture with air.
Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wear personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep away from open flames, hot surfaces and sources of ignition.
Storage conditions	: Store in a well-ventilated place. Keep cool.
Incompatible products	: Strong acids. Strong bases.
Maximum storage period	: ≥ 1 year
Storage temperature	: 5 – 35 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Silver.
Appearance	: Powder.
Odour	: slight.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not available
Flammability	: Flammable solid.
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: 6 – 8
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not applicable
Particle size	: 15 µm
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified.

Aluminium powder (stabilized) (7429-90-5)	
LD50 oral rat	> 15900 mg/kg bodyweight Guideline OECD 401. Source – based on similar product data.
LC50 Inhalation - Rat (Dust/Mist)	0.888 mg/l/4h Guideline OECD 403. Source – literature data.
Silicon dioxide (7631-86-9)	
LD50 oral rat	> 5000 mg/kg bodyweight Guideline EU directive 79/831. Source – literature data.
LD50 dermal rat	> 2000 mg/kg bodyweight Guideline OECD 402. Source – literature data.
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l/4h Guideline OECD 436. Source – literature data.
2-Propanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight Guideline OECD 401. Source – literature data.
LD50 dermal rabbit	13900 mg/kg bodyweight Guideline OECD 402. Source – literature data.
Skin corrosion/irritation	: Not classified pH: 6 – 8
Serious eye damage/irritation	: Not classified pH: 6 – 8
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Silicon dioxide (7631-86-9)	
IARC group	3 - Not classifiable

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Propanol (67-63-0)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

2-Propanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

Aluminium powder (stabilized) (7429-90-5)

NOAEL (oral, rat, 90 days)	90 mg/kg bodyweight/day Guideline OECD 409. Source – based on similar product data.
----------------------------	---

Silicon dioxide (7631-86-9)

NOAEL (oral, rat, 90 days)	4000 mg/kg bodyweight/day Guideline OECD 408. Source – literature data.
Aspiration hazard	: Not classified

Aluminium Pigment ChemTech WZ15

Viscosity, kinematic	Not applicable
----------------------	----------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Aluminium powder (stabilized) (7429-90-5)

NOEC chronic fish	> 50 mg/l Exposure period 96 h. Source – based on similar product data.
NOEC chronic crustacea	0.34 mg/l Exposure period 6 days. Source – based on similar product data.
NOEC chronic algae	≥ 440 mg/l Exposure period 72 h. Guideline OECD 201. Source – literature data.

Silicon dioxide (7631-86-9)

LC50 - Fish [1]	10000 mg/l Guideline OECD 203 Source – literature data.
EC50 - Crustacea [1]	> 5000 mg/l Guideline OECD 202. Source – literature data.
EC50 72h - Algae [1]	> 173.1 mg/l Guideline OECD 201. Source – literature data.
NOEC chronic crustacea	68 mg/l Exposure period 21 days. Test type semi-static. Guideline OECD 211 Source – literature data.

2-Propanol (67-63-0)

LC50 - Fish [1]	10000 mg/l Guideline OECD 203. Source – literature data.
-----------------	--

12.2. Persistence and degradability

No additional information available

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

2-Propanol (67-63-0)

Partition coefficient n-octanol/water (Log Pow)	0.05 Source: ICSC
---	-------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Aluminium Pigment ChemTech WZ15

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1309	UN 1309	UN 1309	UN 1309	UN 1309
14.2. UN proper shipping name				
ALUMINIUM POWDER, COATED	ALUMINIUM POWDER, COATED	Aluminium powder, coated	ALUMINIUM POWDER, COATED	ALUMINIUM POWDER, COATED
Transport document description				
UN 1309 ALUMINIUM POWDER, COATED, 4.1, II, (E)	UN 1309 ALUMINIUM POWDER, COATED, 4.1, II	UN 1309 Aluminium powder, coated, 4.1, II	UN 1309 ALUMINIUM POWDER, COATED, 4.1, II	UN 1309 ALUMINIUM POWDER, COATED, 4.1, II
14.3. Transport hazard class(es)				
4.1	4.1	4.1	4.1	4.1

Aluminium Pigment ChemTech WZ15

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F3
Limited quantities (ADR)	: 1kg
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P002, IBC08
Special packing provisions (ADR)	: PP38, B4
Mixed packing provisions (ADR)	: MP11
Portable tank and bulk container instructions (ADR)	: T3
Portable tank and bulk container special provisions (ADR)	: TP33
Tank code (ADR)	: SGAN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V11
Hazard identification number (Kemler No.)	: 40
Orange plates	:



Tunnel restriction code (ADR)	: E
-------------------------------	-----

Transport by sea

Limited quantities (IMDG)	: 1 kg
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P002
Special packing provisions (IMDG)	: PP38, PP100
IBC packing instructions (IMDG)	: IBC08
IBC special provisions (IMDG)	: B4, B21
Tank instructions (IMDG)	: T3
Tank special provisions (IMDG)	: TP33
EmS-No. (Fire)	: F-G
EmS-No. (Spillage)	: S-G
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: H1
Segregation (IMDG)	: SGG15, SG17, SG25, SG26, SG32, SG35, SG36, SG52
Properties and observations (IMDG)	: If uncoated it possesses the property of evolving hydrogen gas when in contact with water, especially seawater; if treated with oil or wax it does not at ordinary temperatures. Reacts readily with acids and caustic alkalis, evolving hydrogen, a flammable gas. Reacts readily with iron oxide, producing a thermite effect. May form explosive mixtures with oxidizing substances. In the event of breakage of receptacles, the scattered powder is readily ignited by sparks or open flame and may give rise to an explosive atmosphere.

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y441
PCA limited quantity max net quantity (IATA)	: 5kg
PCA packing instructions (IATA)	: 445
PCA max net quantity (IATA)	: 15kg
CAO packing instructions (IATA)	: 448
CAO max net quantity (IATA)	: 50kg
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F3
Limited quantities (ADN)	: 1 kg
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F3
Limited quantities (RID)	: 1kg
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P002, IBC08
Special packing provisions (RID)	: PP38, B4
Mixed packing provisions (RID)	: MP11
Portable tank and bulk container instructions (RID)	: T3
Portable tank and bulk container special provisions (RID)	: TP33
Tank codes for RID tanks (RID)	: SGAN
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W1
Colis express (express parcels) (RID)	: CE10
Hazard identification number (RID)	: 40

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Aluminium, powders	7429-90-5	7603 10 00; ex 7603 20 00	

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds

Aluminium Pigment ChemTech WZ15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Sol. 1	Flammable solids, Category 1
H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.