

TECHNICAL DATA SHEET

Luminous Pigment ChemTech ASG-4EW

TDS Ref.: ASG4EW_TDS
Version: 24/1

Issue date: 2024-09-09

SPECIFIC PRODUCT DATA

Appearance	Powder
Colour when illuminated / Colour in darkness	Yellowish white/ Yellowish green
Material type	Dysprosium and europium doped strontium aluminate
Particle size, μm	5 - 15
Glow time, hours	≥ 12
Afterglow intensity after 10 min, mcd/m^2	≥ 220
Afterglow intensity after 60 min, mcd/m^2	≥ 30
pH (10% aqueous slurry)	9 - 11
Relative density, g/cm^3	3.5 – 3.6
Bulk density, g/cm^3	1.2 – 1.3
Temperature resistance, $^{\circ}\text{C}$	800
Shelf life after the inspection date, years	15

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient name	Identifiers	%
Dysprosium and europium doped strontium dialuminium tetraoxide(monoclinic)	CAS-No.:201426-52-0	≥ 99

DESCRIPTION

The main component of the luminous pigment is strontium aluminate, which belongs to inorganic pigments and has characteristics such as long service life and good glow-in-the-dark effect.

Non-toxic. Chemically resistant in solvents. / Chemically resistant in water and other solvents. Good light stability enables indoor and outdoor application.

The pigment is suitable for various industrial applications. Its concentration depends on an application type and desired effect. The most visible result can be achieved in a transparent and glossy system.

The pigment can be used in combination with other effect materials and colourants.

For more precise recommendations, please contact ChemTech team member.

Standard packaging is a 25 kg carton box with an inner plastic bag. Customised packaging is available.

Luminous pigment should be stored in the original tightly sealed shipping packaging in dry conditions.

ADDITIONAL INFORMATION

The information in this TDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or method of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this TDS information may not be applicable.