

TECHNICAL DATA SHEET

PU Powder ChemTech SFP15T

TDS Ref.: SFP15T_TDS
Version: 24/1

Issue date: 2024-09-10

SPECIFIC PRODUCT DATA

Appearance	Powder
Effect	Opaque
Material type	Polymer
Particle size, μm	15
Relative density, g/cm^3	1.1 – 1.2
Bulk density, g/cm^3	0.6 – 0.7
Oil absorption, g/100g	45 - 55
Shelf life after the inspection date, months	12

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient name	Identifiers	%
Polyurethane	CAS: polymer	96.5 – 97.5
Silicon dioxide	CAS No: 7631-86-9	2.5 – 3.5

DESCRIPTION

The product consists of solid ideally spherical beads made of polyurethane and silicone elastomers with a narrow particle size distribution.

Non-toxic. Chemically resistant in water and other solvents.

The material provides a pleasant tactile and good matting effect, abrasion and scratch resistance, when used in coatings. Its concentration depends on an application type and desired result.

PU powder can be used in combination with other effect materials and colourants.

For more precise recommendations, please contact ChemTech team member.

Standard packaging is a 20 / 25 kg carton box with an inner plastic bag. Customised packaging is available.

PU powder should be stored in the original tightly sealed shipping packaging in dark and dry conditions.

ADDITIONAL INFORMATION

The information in this TDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or method of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this TDS information may not be applicable.